

Push type model HTP

Capacity 500 - 20000 kg

The trolley enables the exact positioning or easy traversing of large loads. It has excellent rolling features due to machined steel wheels mounted on prelubricated, encapsulated ball bearings. The wheels are designed for a max. beam profile incline of 14%.



Features

- Adjustable to fit a wide range of beam widths and profiles.
- Wheel fracture supports and anti-tilt devices are standard.

Optional

- Buffers
- Locking device to secure the unloaded trolley in parking position.
- Rust and acid resistant hand chains.
- Corrosion resistant version.
- Spark resistant equipment.

Model	EAN-No. 4025092*	Capacity kg	Size	Beam flange width b mm	Max. flange thickness t mm	Min. curve radius m	Effort at WLL kg	Net weight* kg	Net weight** with beam brake kg
HTP 500	*054874	500	A	50 - 220	25	0.9	3	8.0	14.5
HTP 1000	*054881	1000	A	50 - 220	25	0.9	6	9.0	17.0
HTP 2000	*054898	2000	A	66 - 220	25	1.15	7	16.0	24.0
HTP 3000	*054904	3000	A	74 - 220	25	1.4	7	32.0	41.2
HTP 5000	*054911	5000	A	90 - 220	25	1.8	9	48.0	58.5
HTP 500	*054928	500	B	160 - 300	40	0.9	3	10.6	17.1
HTP 1000	*054935	1000	B	160 - 300	40	0.9	6	12.0	20.0
HTP 2000	*054942	2000	B	160 - 300	40	1.15	7	19.3	27.3
HTP 3000	*054959	3000	B	160 - 300	40	1.4	7	35.8	45.0
HTP 5000	*054966	5000	B	180 - 300	40	1.8	9	52.2	62.7