




MS

Welded master link

Norm EN 1677-4



Code	Chain Ø				Dimensions in mm				WLL	BF	Weight
	1 leg	2 legs β			A	B	Ø C	E	t	t	Kg
		30°	45°	60°							
MS 13	6/7	-	6	6/7	100	60	13	6.6	1.6	6.4	0.32
MS 16	8	7	7/8	8	120	70	16	6.8	3.1	12.4	0.59
MS 18	10	8	10	10	135	75	18	8.8	4.5	18.0	0.82
MS 20	13	10	-	13	150	90	20	8.8	6.2	24.8	1.14
MS 22	16	-	13	16	150	90	22	11	8.0	32.0	1.41
MS 25	18	13	-	18	170	95	25	13	10.6	42.4	2.03
MS 28	19	-	16	19	200	120	28	13	12.0	48.0	3.02
MS 30	20/22	16	18	20/22	200	120	30	16	15.0	60.0	3.51
MS 36	-	18/19	19/20	-	250	150	36	16	20.0	80.0	6.27
MS 38	26	20	22	26	250	150	38	20	25.0	100.0	7.05
MS 44*	-	22	26	-	280	170	44	20.5	30.0	120.0	9.60
MS 45*	32	26	-	32	300	200	45	22	37.0	148.0	12.12
MS 50**	-	-	32	-	300	200	50	-	50.0	200.0	15.21
MS 55**	-	32	-	-	350	200	55	-	63.0	252.0	20.50
MS 70**	-	-	-	-	400	250	70	-	100.0	400.0	39.30
MS 80**	-	-	-	-	400	250	80	-	125.0	500.0	52.80

* unpainted.

** without flat and unpainted.

Example: Marking of the MS13

8
C E
1 3
C C
Z
Grade 8 CE marking Diameter C Manufacturer symbol Batch